

# DAC 4408-K



The DAC 4408-K in a plastic housing is one of the modular control panels and ensures the activation of SHEV and ventilation drives up to 8 A. Find out more now!

# Performance features

- + Compact SHEV control panel - AdComNet ready
- + Up to 8 A total drive current
- + Stabilised output voltage
- + Switchable SHEV safety functions: Fault equal to alarm, SHEV retrigging function and smoke detector remote reset
- + Option to combine SHEV / building alarm function
- + Integrated comfort functions for daily ventilation
- + 1 slot for an additional module
- + Optional connection to rain detectors or wind / rain sensors without an additional module
- + Connection of up to 2 SHEV operation panels per control panel
- + Min. 72 hr battery backup supply

# Approvals / Certificates

Find out about permission details from your D+H Partner.



# Technical data

## DAC 4408-K

Supply	230 V AC / 50 Hz / 240 VA
Stand-by power	5 W / 6.7 VA
Output	24 V DC / 8 A
Mode of operation monitoring	Continuous duty
Mode of operation Alarm / Ventilation	Short-time duty 30 % duty cycle
Type of protection	IP 32D
Temperature range	-5 °C ... +40 °C
Line / Group	1 / 1
Housing	Plastic
Colour	White (~ RAL 9016)
W x H x D	310 x 310 x 100 mm
Battery type	Typ 8 (2x)
Weight	5.7 kg
Art. No.	30.118.70

Batteries must be ordered separately.

# Example of application

