

CNV control panel - GVL 8304-K
24 V DC / 4 A / 1 ventilation group**Performance features:**

Compact ventilation control panel for controlling 24 V DC window drives.
For 4 A drive current in one group.
Ventilation safety function (storage operation OPEN/CLOSED) can be hard-coded.
Possibility of single/ or central switching (OPEN / CLOSED).
Input for external controller, e.g. timer.
Optional connection of rain detectors or wind / rain sensors without an additional module.
Surface-mounted design.

Technical data:

Supply: 230 V AC / 50 Hz / 120 VA
Stand-by power: 4.3 W
Output: 24 V DC / 4 A
Mode of operation: Short-time duty 20 % duty cycle
Type of protection: IP 50
Temperature range: -5 °C ... +40 °C
Group(s): 1
Housing: Plastic
Colour: Light grey (~ RAL 7035)
W x H x D : 172 x 151 x 95 mm
Weight: 2 kg

Scope of supply:

Ventilation control panel, instruction for use

Brand: D+H

Type: GVL 8304-K

Art. No.: 30.202.10

Quantity: pcs Price: EUR TP: EUR

<https://www.dh-partner.com/int/en/service/planning-support>

Important information:

This product description does not constitute a tender. The responsibility for compliance with public procurement law requirements lies with the tendering planner or architect.

Installation and commissioning in accordance with the manufacturer's instructions.

Subject to technical changes.