

GVL 8401-K-RC V2



Can also be used via wireless remote control: The GVL 8401-K-RC V2 can be activated wirelessly, increasing user convenience.

Performance features

- + Compact ventilation control panels with an integrated wireless receiver for controlling 24 V DC window drives
- + Up to 1 A total drive current
- + 2 ventilation groups
- + Optional individual and/or control circuit (OPEN / CLOSED)
- + Configurable ventilation safety function (storage operation OPEN / CLOSED)
- + Freely programmable group assignment for central inputs (weather, time, etc.)
- + Operation via wireless remote control (Multiple control panels can be controlled with one remote control)
- + 868 MHz radio frequency, permitted throughout the EU
- + High level of security against external control - 24 bit address code and transmitting code change at each button press (hopping code)

Technical data

GVL 8401-K-RC V2

Supply	230 V AC / 50 Hz / 56 VA
Stand-by power	< 1 W
Output	24 V DC / 1 A
Mode of operation	Short-time duty 20 % duty cycle
Type of protection	IP 66
Temperature range	-5 °C ... +40 °C
Group(s)	2
Housing	Polypropylene
Colour	Light grey (~ RAL 7035)
W x H x D	180 x 130 x 77 mm
Weight	0.97 kg
Art. No.	30.241.90

Example of application

