

- 1 D+H Mechatronic (english)**
- 1.1 DAC-M Series - ONLY FOR FRANCE**
- 1.1.1 SHEV control panel - compact - DAC 4404-MS**

24 V DC / 4 A / 2 lines / 2 drive groups**Performance features**

SHEV controller - AdComNet ready;
SHEV control - AdComNet ready;
Approval according to EN 12101-10 and certified according to NF 537, developed according to ISO 21927-9;
Stabilised output voltage;
Connection of up to 4 SHEV operation panels per control panel;
Min. 72 hr battery backup supply;
Temperature-controlled battery charge;
Batterie charge and status check;
SHEV retriggering function;
Codable SHEV and ventilation functions;
Combination of a SHEV- / building alarm function possible;
Comfort ventilation functions;
Line monitoring for short circuit and interruption;
Slot for additional module;
Possible connection for optical and acoustical alarm devices;
LED status display visible from outside;
Usable for daily ventilation;
Ventilation time and opening width adjustable;
Wind/rain sensor connectable without additional module;

Technical data:

Supply: 230 V AC / 50 Hz / 120 VA
Stand-by power: 6.8 W / 22 VA
Output: 24 V DC (21.6 - 28.5 V DC) / 4 A
Ripple: < 2 Vss
Mode of operation
-Monitoring: Continuous duty
-Alarm / Ventilation: Short-time duty (30 % duty cycle)
Type of protection: IP 32D
Temperature range: -5 °C till +40 °C
Line / Group: 2 / 2
Housing: Steel sheet
Colour: Light grey (~ RAL 7035)
Dimensions (WxHxD): 400 x 300 x 120 mm

Scope of supply:

Control panel with steel sheet housing incl. keys, without batteries (batteries must be ordered separately)

Brand: D+H Mechatronic AG

Type: DAC 4404-MS

[Planning Support](#)

Artikelnr.: 30.118.55

Quantity: **Stk** **Preis:** **€** **TP:** **€**

