

- 1 D+H Mechatronic (english)**
- 1.1 RC Series**
- 1.1.1 Wireless receiving module - RCM 024-11-U**

24 V DC / 0.03 A
for D+H control panels, 2 control outputs

Performance features:

Wireless receiver with security encryption and code hopping principle;
Up to 10 D+H wireless remote controls can be assigned;
High level of security against external control - with 128-bit AES encrypted authentication;
For all 24 V DC D+H control panels;
2 group control outputs for connecting to the control panel ventilation button inputs;
For installing in 55 mm flush-mounted socket (not included);

Technical data:

Supply: 24 V DC
Current consumption: < 0.03 A
Switching current: max. 0.05 A
Type of protection: IP 30
Temperature range: -5 °C till +60 °C
Radio frequency: 868.3 MHz, FSK
Encryption: AES / 128 Bit
Wireless standard:
ETSI EN 300220-1:2010
ETSI EN 301489-1:2011
ETSI EN 301489-3:2002
Housing: Plastic
Colour: Grey
Dimensions (WxHxD): 50 x 48 x 19 mm

Scope of supply:

Wireless receiving module, instruction for use

Brand: D+H Mechatronic AG
Type: RCM 024-11-U

[Planning Support](#)

Artikelnr.: 30.554.60

Quantity: **Stk** **Preis:** **€** **TP:** **€**